

Language: English • français • italiano • português • español ****

==== Contents ====

- * 1 Format
- * 2 DTD

The .q3d file format is an method of storing query definitions as XML, ensuring that they are both human- and machine-readable. Inspect3D allows users to save query definitions from the  **Group Definition** dialog. Previously-saved query definitions can be loaded and applied to the CMO library to populate groups in the Group Definition dialog or from the Group Definitions drop-down menu's  **Load Group Def & Compute Groups** option.

Format

As an XML document, a .q3d file is made up of hierarchical elements that are demarcated by tags, indicated by the < and > characters. An element consists of a start tag, <elementname>, and end tag, </elementname>, and all of the characters in between. Alternatively, an element can be defined by a single tag, <elementname />.

Tags can also contain attributes in the *name="value"* format, further describing the associated element.

1. The top-level element in a .q3d file is *queries*. It contains an arbitrary (1-n) number of *query* elements.
2. The second-level element in a .q3d file is *query*. A *query* element has a *name* attribute (the corresponding group's name) and contains an arbitrary (1-n) number of *Definition* elements.
3. The bottom-level element in a .q3d file is *Definition*. A *Definition* element consists of a single tag and encodes a single sub-group via a number of attributes.

DTD

Formally, a .q3d file respects the Document Type Definition (DTD):

```
<!DOCTYPE queries [
  <!ELEMENT queries query+>
  <!ENTITY query Definition+>
  <!ATTLIST query
    name CDATA #REQUIRED
  >
  <!ENTITY Definition>
  <!ATTLIST Definition
    condition CDATA #REQUIRED
    query CDATA #REQUIRED
    workspace CDATA #REQUIRED
```

```
type CDATA #REQUIRED
folder CDATA #REQUIRED
name CDATA #REQUIRED
component CDATA #REQUIRED
max_elements CDATA #REQUIRED
negate_result CDATA #REQUIRED
events CDATA #REQUIRED
exclude_events CDATA #REQUIRED
has_tag_ref CDATA #REQUIRED
tag_logic CDATA #REQUIRED
tag CDATA #REQUIRED
has_subject_ref CDATA #REQUIRED
subject CDATA #REQUIRED
normalize_info CDATA #REQUIRED
>
]>
```

Retrieved from ""

From:
<https://has-motion.com/wiki/> - **Wiki Documentation Site**

Permanent link:
https://has-motion.com/wiki/doku.php?id=inspect3d:documentation:files:q3d_query_file&rev=1718385540

Last update: **2024/06/14 17:19**

