

Allows multiselection of C3D motion files and frame offsets for synchronized playback.

```
Set_Animate_Multiple_Files
/PRIMARY_FILE_NAME=
/PRIMARY_EVENT_SEQUENCE=
/PRIMARY_EXCLUDE_EVENTS=
/PRIMARY_X_OFFSET=
/PRIMARY_Y_OFFSET=
/PRIMARY_Z_OFFSET=
/FILE_NAME=
/EVENT_SEQUENCE=
! /EXCLUDE_EVENTS=
! /VIEW_DIALOG=TRUE
/X_OFFSET=
/Y_OFFSET=
/Z_OFFSET=
/COLOR=
;
```

The Command parameters are divided into the primary and secondary.

Primary is the active file in the workspace. // Secondary are the additional files to be synchronized.

PRIMARY_FILE_NAME // Sets the active file in the animation viewer // /PRIMARY_EVENT_SEQUENCE= // /PRIMARY_EXCLUDE_EVENTS= // An event sequence for the primary file. Only the first instance of the event sequence will be used. // /PRIMARY_X_OFFSET=// /PRIMARY_Y_OFFSET=// /PRIMARY_Z_OFFSET=// If the primary offset is blank or is set to a number, the number is the offset Using an expression is a special case. The expression doesn't see an offset per se, but it sets a based value which is subtracted from the offset of the secondary files.

Secondary are the additional files to be synchronized. /FILE_NAME= /EVENT_SEQUENCE= ! /EXCLUDE_EVENTS= ! /VIEW_DIALOG=TRUE /X_OFFSET= /Y_OFFSET= /Z_OFFSET= /COLOR=

Example

```
Set_Animate_Multiple_Files
/PRIMARY_FILE_NAME=*R_0001.c3d
/PRIMARY_EVENT_SEQUENCE=RHS+RHS
! /PRIMARY_EXCLUDE_EVENTS=
/PRIMARY_X_OFFSET=0.1
/PRIMARY_Y_OFFSET=0.2
/PRIMARY_Z_OFFSET=0.3
/FILE_NAME=*R_0002.c3d+*R_0003.c3d
/EVENT_SEQUENCE=RHS+RHS
! /EXCLUDE_EVENTS=
! /VIEW_DIALOG=TRUE
/X_OFFSET=0.2
/Y_OFFSET=0.3
/Z_OFFSET=0.4
/COLOR=RED+BLUE
```

;

From:

<https://has-motion.com/wiki/> - Wiki Documentation Site

Permanent link:

https://has-motion.com/wiki/doku.php?id=set_animate_multiple_files&rev=1728420214

Last update: **2024/10/08 20:43**

