

Import_Data_From_Matfile

Overview

Imports specified signals from a Matfile. This function expects the .mat file to have a specific input. For example, within MATLAB, we write and run the following script:

Pipeline Command

```
Import_Data_From_Matfile  
/SIGNAL_TYPES=  
!/SIGNAL_FOLDER=PROCESSED  
/SIGNAL_NAMES=  
/FILE_NAME=  
/MATLAB_NAMES=  
;
```

Examples

```
array = linspace(0,10,100);  
importThisData = {sin(array)};  
  
FRAME_RATE{1,1} = 180;  
ANALOG_VIDEO_FRAME_RATIO{1,1} = 0;  
FILE_PATH = {'C:\Users\Public\MATLAB\Sub01_Walk001.c3d'};  
  
matDirectory = 'C:\Users\Public\MATLAB\Sub01_Walk001.mat';  
save(matDirectory, 'importThisData', 'FILE_PATH', 'FRAME_RATE', 'ANALOG_VIDEO_FR  
AME_RATIO', '-v6')
```

What is really important is the FILE_PATH. Within your Visual3D workspace, you will presumably have loaded some .c3d files (in this case, Sub01_Walk001.c3d). The address under FILE_PATH must match the location of the original .c3d files, even if that path is different from the path of the Visual3D workspace. If the Import_Data_From_Matfile command executes but doesn't create or populate a folder in the Visual3D workspace, check the FILE_PATH.

FILE_PATH is different from FILE_NAME, which should be the path to the .mat file you wish to import data from.

From:
<https://has-motion.com/wiki/> - Wiki Documentation Site

Permanent link:
https://has-motion.com/wiki/doku.php?id=visual3d:documentation:pipeline:file_commands:import_data_from_matfile&rev=1757705667

Last update: 2025/09/12 19:34

