

Metric Compute Confidence Ellipse

Overview

The **Metric Compute Confidence Ellipse** command can be used to compute the 95 % confidence ellipse in 2 or more dimensions. This is the smallest ellipse that will cover 95 % of the data points.

Can also be used to compute the area or volume of an ellipse based on PCA. Does not require all vertices to be present for all frames. It can be found within the **Pipeline Workshop** under **Metric**.

Pipeline Command

The syntax for the function is as follows:

```
Metric_Compute_Confidence_Ellipse
/SIGNAL_TYPES=
! /SIGNAL_FOLDER=ORIGINAL
! /SIGNAL_NAMES=
! /COMPONENT_SEQUENCE=
! /RESULT_FOLDER=PROCESSED
/RESULT_NAME=
! /EVENT_SEQUENCE=
! /EXCLUDE_EVENTS=
! /START_FRAME=
! /END_FRAME=
;
```

Command Parameters

The Parameters for the function are as follows:

/SIGNAL_TYPES=	Specify signal type
/SIGNAL_NAMES=	Specify signal name
/SIGNAL_FOLDER=	Specify signal folder
/COMPONENT_SEQUENCE	Which component of the signal will be used for statistical analysis of the sequence.
/RESULT_FOLDER	Name of folder holding resulting processed data
/EVENT_SEQUENCE=	Specify the sequence of Events. Any number of Events can be entered (separated by +). This specific sequence of events must be true for a metric to be computed. The metric is computed from the first event in the sequence to the last event in the sequence
/EXCLUDE_EVENTS=	If this event occurs before the first and last event, do not compute a metric

/START_FRAME=	The frame at which to start recording data.
END_FRAME=	The frame at which to stop recording data.

Dialog

The command can be edited in a text editor or in a dialog form. To edit in the dialog pop up form either click on the **Edit** button in the pipeline workshop or double-click on the pipeline command. The dialog is shown below.

The dialog box allows you to assign values to the command parameters outlined above.

Example: Computing Confidence Ellipse for COFP

In this example the **Metric Compute Confidence Ellipse** command is used to compute the values associated with the confidence ellipse for left and right COFP during a balance trial. This analysis can be useful to compare balance consistency between sides using ellipse areas.

The pipeline command for each side is:

```
Metric_Compute_Confidence_Ellipse
/SIGNAL_TYPES=COFP
! /SIGNAL_FOLDER=ORIGINAL
/SIGNAL_NAMES=FP3
/COMPONENT_SEQUENCE=X + Y
! /RESULT_FOLDER=PROCESSED
```

```

/RESULT_NAME=Ellipse_Right
/EVENT_SEQUENCE=START+END
! /EXCLUDE_EVENTS=
! /START_FRAME=
! /END_FRAME=
;

Metric_Compute_Confidence_Ellipse
/SIGNAL_TYPES=COFP
! /SIGNAL_FOLDER=ORIGINAL
/SIGNAL_NAMES=FP4
/COMPONENT_SEQUENCE=X + Y
! /RESULT_FOLDER=PROCESSED
/RESULT_NAME=Ellipse_Left
/EVENT_SEQUENCE=START+END
! /EXCLUDE_EVENTS=
! /START_FRAME=
! /END_FRAME=
;

```

The resulting metric is found in the **METRIC:PROCESSED** folder and should look similar to below.

File	Item	X	Y	Z
Balance_SmartCell_Eyes...	1	0.000012	-0.141393	0.192856
-	2	0.002255	0.165078	0.986280
-	3	0.000290	-0.986280	0.165078

The metric for this example contains 3 components, with 3 values for each component. The results are as follows:

Frame 1:

X	Volume
Y	average of all frames of input component 1
Z	average of all frames of input component 2

Frame 2: (for input component 1) 1: Eigenvalue 2: eigenvector 3: eigenvector Frame 3: same as

frame 2, but for input component 2

If you have two input components, frame 1 X is the area, if you have three input components, Frame 1, X is the volume.

The ellipse can also be visualized in the reports tab:

Add a new 2D Graph to your report with the appropriate X and Y data and make sure to select **Graph Confidence Ellipse**.

Add New 2D Graph

Location
Page: 1
Pos.: 1
Column: 1
Row: 2

Titles
Font: Arial
Title: Both
X Axis Label: meters
Y Axis Label: meters

X Axis Data
Type: DERIVED
Folder: COP
Name: COP_1
Component: 1

Y Axis Data
Type: DERIVED
Folder: COP
Name: COP_1
Component: 2


X Axis Range
☒ Graph within a range of events
☐ Graph within Event_Sequence
Range Begin: Start
Range End: End

Line Style
Line Style: NULL
☐ Graph Mean
☐ Graph Standard Deviation
☐ Graph Points
☒ Graph Confidence Ellipse

Legend Text
Control

Buttons: OK, Cancel, Preview, Help

The resulting graph should look similar to below:



Notes

For more information see, [confidence hyper ellipse eigenvalues](#).

Resulting Signal, Frame 1 contains volume and average value

Starting at frame 2, one frame for each dimension containing the eigenvalue and eigenvector (e.g. scale and unit vector)

From:
<https://has-motion.com/wiki/> - Wiki Documentation Site

Permanent link:
https://has-motion.com/wiki/doku.php?id=visual3d:documentation:pipeline:metric_commands:metric_compute_confidence_ellipse&rev=1761937629

Last update: 2025/10/31 19:07

