

extracting metric values from vicon's .mp file into visual3d subject/data metrics

pipeline command

get_vicon_model_metric ! /calibration_file= ! /mp_file_name= ! /metric_names= ! /metric_values= ;
/calibration_file refers to the link model in which the metrics will be stored if calibration_file is empty or =*, the current link model is used. /mp_file_name refers to the vicon mp file if mp_file_name is empty, the user is prompted for the filename. mp_file_name refers to the full path name of the file. /metric_names and /metric_values are optional if metric_names is empty or =*, all metric_names in the .mp file are selected if metric_values is populated, this is the default value of metric_names and is used if metric_names does not exist in the .mp file.

example

given an mp file containing the following information:

\$rknee_width = 150.0 \$rfoot_width = 100.0 \$lknee_width = 150.0 \$lfoot_width = 100.0 and the command

'get_vicon_model_metric /calibration_file=* /mp_file_name= /metric_names= /metric_values= /name_prefix= ;

- the current active model will be used.
- the user will be prompted for the mp file name.
- all 4 metric values in the mp file will be added to the model subject metrics
- no prefix will be added to the names.

get_vicon_model_metric /calibration_file= /mp_file_name= /metric_names=rhip_radius
/default_metric_values=0.5*distance(right_hip,left_hip) /name_prefix= ;

- rhip_radius is not part of the mp file
- a default metric value has been provided
- a model metric rhip_radius will be created (or modified)
- the value of the metric will be the expression 0.5*distance(right_hip,left_hip)

From:
<https://has-motion.com/wiki/> - Wiki Documentation Site

Permanent link:
https://has-motion.com/wiki/doku.php?id=visual3d:documentation:pipeline:model_commands:get_vicon_model_metric&rev=1718801525

Last update: 2024/06/19 12:52

