

Description: Allow accessing pipeline parameter “array values” by “index”.

```
Get_Pipeline_Parameter_Index_Value
/PARAMETER_NAME=
/PARAMETER_VALUE=
/INDEX=
;
```

Example

```
Set_Pipeline_Parameter
/PARAMETER_NAME=running_speed
/PARAMETER_VALUE=10 km/h+12 km/h+14 km/h
;

Set_Pipeline_Parameter
/PARAMETER_NAME=filenames
/PARAMETER_VALUE=fileA + fileB + fileC
;

For_Each
/ITERATION_PARAMETER_NAME=file
/ITERATION_PARAMETER_COUNT_NAME=increment
/ITEMS=filenames
;
    File_Open
    /FILE_NAME=::file
    ;
    Get_Pipeline_Parameter_Index_Value
    /PARAMETER_NAME= SCOTT
    /PARAMETER_VALUE=::running_speed
    /INDEX=::increment
    ;

    Assign_Tags_To_Files
    /MOTION_FILE_NAMES=::file
    /TAGS=::SCOTT
    ;
End_For_Each
/ITERATION_PARAMETER_NAME=file
;
```

Retrieved from “”

From:
<https://has-motion.com/wiki/> - **Wiki Documentation Site**

Permanent link:
https://has-motion.com/wiki/doku.php?id=visual3d:documentation:pipeline:pipeline_commands:get_pipeline_parameter_index_value&rev=1718644085

Last update: **2024/06/17 17:08**

