

Typical_Processing_Session

This tutorial covers the basic processing steps starting from C3D files through to report generation. None of these steps will be described in detail, but we will provide links to pages with more detailed descriptions.

As a starting point, we will assume that you have:

- a model template (MDH)
- a signal processing pipeline (V3S)
- a report template (RGT)
- a static trial (C3D)
- multiple movement trials (C3D)

If you don't have these templates or pipelines, you can download the sample files or follow the links to documentation on how to create them.

You can download sample C3D files to use with this tutorial [here](#).

Creating a model

To create the model, make sure that Visual3D is started by selecting **Start → Programs → C-Motion → Visual3D**

1. Load the static C3D file by going to Model → Create (Add Static Calibration File) → Hybrid Model from C3D file .	
2. Select "LowerBodyStaticTrial01.c3d." Click Open .	
Visual3D will switch to Model Building mode automatically. The 3D viewer will display the average value of the marker locations from the standing file. The dialog bar to the left of the screen will contain a list of segments, which by default will contain only a segment representing the Laboratory (e.g. Motion Capture Volume).	

Note: Your screen may look slightly different.

Applying a model template

In this section, you will apply a previously constructed model template. If you don't have a [model template](#) (.mdh file) for this standing trial, please complete the [Model Building Tutorial](#) which describes the process for building a model and creating a template.

If you have a model template, then:

1. Apply the model template:

1a. Go to Model → Apply Model Template

1a. In the dialog, select the model template “”

2. Set the subject height/weight:

2a. In the models tab, go to **Subject Data/Metrics**

2b. Double click on the value next to Mass listed under Expression

2c. Double click on the value next to Height listed under Expression

Using a Pipeline Command

Pipeline commands can be used to apply the model template and set the subject height/weight. These commands can be edited to look for specific files, or if parameters are left blank, they will prompt the user for relevant information.

1. [Apply Model Template](#) command 2. [Set Subject Height](#) command 3. [Set Subject Weight](#) command A great example of applying a model template can be found on the following pages [Pipeline Processing Example 1](#) and [Pipeline Processing Example 2](#).

Opening movement files

This section will open/add the movement files to the model that was created in the previous sections on this page.

If you were able to successfully load the static trial and apply the model template by following the steps above, the static trial should appear in the Workspace tab.

This means you are ready to continue onto the next step.

1. Load the dynamic trials

a. File → Open/Add...

b. Select **Insert new files into your currently open workspace**

c. Select “WalkingTrial_01.c3d”

Verify - Verify the model file named *WalkingTrial_01.c3d* appears in the column labeled **Motion Files**. Visual3D displays the [active file](#) in the Motion Files column, but not directly beside the static trial file.

Verify - Click on the **Signal and Event Processing** Tab. The viewing area will open. At this point, the movement trial has not been associated (or mapped) to the model trial. In the viewing area, only the markers will be animated.

Note: If no image appears, verify that there is a single active file in the file name box.

To activate the animation, click on the arrowhead PLAY  button at the bottom of the screen. The marker figure should walk across the screen. However, no bones will appear.

Using a Pipeline Command

The dynamic trials can be opened using the [File_Open](#) command.

A great example of assigning models to motion files can be found on the following pages [File Open](#).

Assigning movement files to a model

In the previous sections, the movement files were added and the model template was applied to the static standing trial. These movement files need to be associated or assigned with static standing model file. When movement files are assigned to a model, the pose (position and orientation) of each segment and landmarks in the model are computed for the motion file. To assign the movement files to a model, follow these steps:

1. Assign model to motion trial

- Model → Assign Model to Motion Files
- Select the checkbox next to WalkingTrial_01.c3d
- Click OK

Verify - The 3D Animation Viewer should now display a skeleton of the lower body that has been associated with your movement data. You can animate the skeleton by clicking the PLAY  button in the VCR controls at the bottom of your screen.

Pipeline command for assigning a model

The model can be assigned to the movement trials using the [Assign_Model_File](#) command.

A great example of assigning models to motion files can be found on the following page [Assign_Model_File](#).

Basic Signal Processing

Signal Processing is accomplished typically through [pipeline commands](#). For more detail, a tutorial describing [Signal Processing](#) is available.

This section assumes that you have worked through the previous sections on this page. The following are steps for Interpolating and Filtering the **TARGET** data.

Make sure you are in the Signals and Events tab for the Processing section

1. Interpolate **TARGET** signals:

- a. Signals and Events tab
- b. Expand the **TARGET** folder
- c. Right click on the **ORIGINAL** folder
- d. Click Processing >
- e. Click Interpolate
- f. Click Done

See [Signal Processing](#) for an explanation of the default command parameters.

Note that a **PROCESSED** folder has appeared under the **TARGET** folder in the data tree.

2. Filter **TARGET** signals:

- a. Expand the **TARGET** folder
- b. Right click on the **PROCESSED** folder
- c. Click Processing >
- d. Click Filter
- e. Click Done

See [Processing](#) for an explanation of the default command parameters.

Note that only a **PROCESSED** folder exists under the **TARGET** folder in the data tree (e.g. a new **PROCESSED** folder wasn't created). By default Visual3D uses only one **PROCESSED** folder, which contains the most recent processing done to a signal.

3. Review Processing History:

- a. Expand the **TARGET** folder
- d. Expand the **PROCESSED** folder
- c. Left click on signal "CTRHID"
- d. In the Data View Dialog, select Signal Processing History tab

Pipeline commands for Basic Signal Processing

Signals can be interpolated and filtered using the [Interpolate](#) and [Lowpass_Filter](#) commands.

Refer to [Tutorial:_Command_Pipeline#Pipeline_SIGNAL_PROCESSING](#) for an example.

Check Force Assignments

Creating Event Labels

An Event is simply an occurrence of interest that correlates to a motion capture frame, i.e. to a particular time point within a movement. The key events for gait studies (e.g., heel strike, toe-off) are now so well standardized that Visual3D can detect and mark them automatically. For other applications, you can define your own events, either manually (using the mouse to double-click on significant points on any graph) or computationally. After you have worked through the steps in this section, refer to [Tutorial:_Event_Processing](#) for more information about creating event labels. In addition, go to [Event Labels](#) for more examples.

Entering an Event manually

Events can be added to the data file manually by selecting a frame in a graph in **SIGNAL AND EVENT PROCESSING** mode. Follow these steps:

1. Plot the signal as an Interactive Graph:

- a. In the Signal and Events tab
- b. Expand the TARGET folder
- c. Expand the PROCESSED folder
- d. Right click on the LFCC target
- e. Select "Graph X, Y and Z" >
- f. Click New Graph

Select the graph by clicking with the Left Mouse Button on the graph. When the graph is selected you will see the handles (little rectangles) on the graph.

When the graph is selected you can change the scale for the X and Y axes.

You can also view a vertical line which is associated with the current frame.

2. Manually create a new Event Label

- a. Double click with the Left Mouse button at the location you want the event to be added
- b. In the dialog, specify the event label name

Note that the name of the Event Label can be the same as an existing label in the data tree because more than one occurrence of an Event is allowed.

The buttons « and » allow you to move the Event forward or backward through the frames.

After an Event has been created it can be edited using the Edit Events Dialog. The process of Editing an Event is explained elsewhere.

Entering an Event manually via the pipeline

This example created an explicit event which can also be done using the [Event_Explicit](#) command.

If you are processing gait, you will want to use the [Automatic_Gait_Events](#) command.

Users can create events specific to their task (different types of motion, EMG processing, etc.) by using any combination of signal processing in conjunction with the many [Event commands](#).

Creating model based items

Model Based Items refers to Kinematic and Kinetic calculations based on rigid body modeling.

In this section, we will create a knee joint angle. After you have worked through this section, refer to the [Compute Model Based tutorial](#) which describes the basics for creating model based items. One of the more important sections describes the interpretation of the [knee joint angle](#).

Create a joint angles for the Right and Left Knee

To create the right knee joint angle, follow these steps:

1. Under MODEL in the main menu bar, select Compute Model Based Data	
2. Define the Right Knee Angle as follows	
1. Data Name: RKneeAngle	
2. Model Based Item Properties: JOINT_ANGLE	
3. Segment: RSK (Right Shank)	
4. Reference Segment: RTH (Right Thigh)	
5. Cardan Sequence: XYZ	
6. Click Create	
Processing Results	
- The joint angle is created and a processing dialog shows if any errors were encountered. Note that the dialog also contains which files were processed. It is important to note this because signals are only created for the active files.	

3. Define the Left Knee Angle as follows

1. **Data Name:** LKneeAngle

2. **Model Based Item Properties:** JOINT_ANGLE

3. **Segment:** LSK (Left Shank)

4. **Reference Segment:** LTH (Left Thigh)

5. **Cardan Sequence:** XYZ

6. Click **Create**

Notice that a new folder is created in the Data Tree for LINK_MODEL_BASED calculations. This folder now contains the Left Knee Angle and Right Knee Angle Signals.

Using Pipeline Commands

Pipeline commands can be used to create the model based data. The following commands will create the left and right knee angles:

```
Compute_Model_Based_Data
/RESULT_NAME=Right Knee Angle
/FUNCTION=JOINT_ANGLE
/SEGMENT=RSK
/REFERENCE_SEGMENT=RTH
/RESOLUTION_COORDINATE_SYSTEM=
! /USE_CARDAN_SEQUENCE=FALSE
! /NORMALIZATION=FALSE
/NORMALIZATION_METHOD=TRUE
! /NORMALIZATION_METRIC=
! /NEGATEX=FALSE
! /NEGATEY=FALSE
! /NEGATEZ=FALSE
! /AXIS1=X
! /AXIS2=Y
! /AXIS3=Z
;
```

```
Compute_Model_Based_Data
/RESULT_NAME=Left Knee Angle
/FUNCTION=JOINT_ANGLE
/SEGMENT=LSK
/REFERENCE_SEGMENT=LTH
/RESOLUTION_COORDINATE_SYSTEM=
! /USE_CARDAN_SEQUENCE=FALSE
! /NORMALIZATION=FALSE
/NORMALIZATION_METHOD=TRUE
! /NORMALIZATION_METRIC=
! /NEGATEX=FALSE
! /NEGATEY=FALSE
```

```
! /NEGATEZ=FALSE
! /AXIS1=X
! /AXIS2=Y
! /AXIS3=Z
;
```

Creating a Report

Once signals have been created, they can be added to a report. The report allows users to preview their data prior to exporting, or to share data (ex. a clinician).

An example of a report may be seen on the right. The [Report Building Tutorial](#) describes the process for creating this report.

Note: It is possible to add and overlay more than one item per graph so that direct comparisons between different variables can be made.

Pipeline commands

A report may be saved as a .rgt file. The report may then be opened and applied to other subjects. The .rgt file also contains the signal definitions (the signals created using the Compute Model Based dialog/pipeline command). The [Model Building Tutorial](#) describes how to create a report and [save](#) it as a .rgt file.

Graphs can also be created using the [Make_Line_Graph](#) command. This dialog does not currently have a dialog, so it is highly recommended to familiarize yourself with the options using the dialog prior to using the command.

Updating the Model Based Computations and Graphs via Recalc

If any modification has been made to the Visual3D workspace once the Model Based Computations and Graphs have already been created, it is recommended to execute the [Recalc pipeline](#) to update the .CMO Workspace. This will Recalculate the link model, event dependencies, and execute the RECALC Pipeline.

Detailed information on the Recalc pipeline can be found [here](#).

From:
<https://has-motion.com/wiki/> - Wiki Documentation Site

Permanent link:
https://has-motion.com/wiki/doku.php?id=visual3d:tutorials:knowledge_discovery:typical_processing_session&rev=1721158419

Last update: 2024/07/16 19:33

